Environmentally friendly photosensitive sensor

Product specifications

Customer	
Date	
Model	LLS05-H ML
Product number	

Make	
Approval	
Customer Signatures	

森霸传感科技股份有限公司

Sales center

Address: 32nd Floor,Tower T3,One Excellence,No.5109Menghai Avenue,Nanshan District, Shenzhen, China

Website www.nysenba.com

Tel 86-755-82594756 18929323299

Fax 86-755-82594762

■

Product function

1. (CdS) ROHS
Replace Photoresistors(Cds),RoHS Compliance/Pb-free/Cd-free.
2. LCD
adjust background light automatically,LCD,mobile phone,camera,Computer Camera etc.
3.
Suitable for all kinds of light control products and light control toys,such as night lamp etc.
4.
Applicable to all kinds of infrared monitoring products

■

Product Features

1. 520nm
Peak sensitive wavelength 520nm
2.
Low Power Consumption
3.
High reliability
4.
Perfect consistency, completely solve the problems of early start or poor consistency of the lamp.
5. +85 /65% 1000H
Fast response, stable performance, no drift at 1000h starting point under + 85 / 65% humidity condition
6.
Size customized, easy for Installation.

森霸传感科技股份有限公司


■ Product Dimensions


× ñ F

■ Ta=25 MAXIMUM RATING (TA = 25 ° C)

Parameter name	Symbol	Rating	Unit


■ Reference circuit






泰霸传感科技股份有限公司


■ Typical photoelectric characteristics curves




Change of illuminance and photocurrent



Photowavelength map



Temperature and photocurrent diagram



Temperature and dark current diagram

森霸传感科技股份有限公司

■

■ **Recommended Soldering Conditions**

Mode		Condition
Manually Soldering	Soldering Iron Temperature	340 0 Max340 (power:60Wmax)
	Soldering Time	3
	Soldering Position	1.5mm 1.5

■ Precautions

1. 0 +30°C 70% 3 3

The storage conditions of the product after leaving the factory shall be 0 to + 30 ° C, the relative humidity shall not be more than 70%, and the storage period shall be 3 months. If the storage period is more than 3 months, the product shall be placed in a closed container with nitrogen or desiccant, and the storage period may be up to one year

2. 0 +30°C

Once the package is opened, the products should be used up as soon as possible . If it is not used up,It should be sealed immediately. The storage condition is 0 +30°C, and the relative humidity ≤ 60%. It should be used up within one week

3.